

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016
Supersedes Date: No information available
Version 2

V 61 3101

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name Bostiks Best Wood Floor Adh.

Product Code G64130 BBWFA

Product(s) Covered

A38910 BH BEST CARTRIDGES 24X10.1/C
A38921 BH BEST CARTRIDGES 12X28
A39000 BOSTIK BEST 12/10.1 OZ. CTG

G64130-BU BH BEST 5G

G64130-BUC BEST/METAL/PAIL/5GL/24PP/CAN G64140-95L BOSTIKBEST/DRM/52GL/VRWTLB/3PP

G64140-DZ BH BEST 5G

G64140-DZC BH BEST 5G CANADA

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Adhesives, sealants.
Uses Advised Against No information available

1.3. Details of the Supplier of the Safety Data Sheet

Company Name

Bostik, Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1 (800) 843-0844 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

Fax: +1 (414) 774-8075 Email: msds@bostik-us.com

1.4. Emergency Telephone Number

Emergency Telephone Telephone: 1-800-227-0332

(Outside U.S.) 1-703-527-3887

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the Substance or Mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Reproductive Toxicity	Category 1B
Flammable Liquids	Category 4

2.2. Label Elements

EMERGENCY OVERVIEW

G64130 BBWFA Bostiks Best Wood Floor Adh.

Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

DANGER

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction May damage fertility or the unborn child Combustible liquid



Appearance Paste

Physical State Liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see first aid measures on this label)

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

Not applicable

Unknown Toxicity

23.15% of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Causes mild skin irritation.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	CAS No	Weight-%
Limestone	1317-65-3	30 - 60
Naphtha, petroleum, heavy alkylate	64741-65-7	3 - 7
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - 1
Dibutyltin dilaurate	77-58-7	0.1 - 1
Quartz	14808-60-7	0.1 - 1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General Advice Remove and isolate contaminated clothing and shoes. In the case of skin irritation or

allergic reactions see a physician.

Eye contact In case of contact with substance, immediately flush skin or eyes with running water for at

least 20 minutes. If eye irritation persists: Get medical advice/attention.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call

a physician.

Inhalation Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. If symptoms persist, call a

physician.

Self-protection of the First Aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms No information available.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians Treat symptomatically. May cause sensitization by inhalation and skin contact.

4.4. Reference to Other Sections

Reference to Other Sections SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 11: TOXICOLOGY INFORMATION

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

5.2. Special Hazards Arising from the Substance or Mixture

Specific Hazards Arising from the Chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

5.3. Advice for Firefighters

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

All equipment used when handling the product must be grounded. Do not touch or walk

through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.2. Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

6.3. Methods and Material for Containment and Cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers. Dike far ahead of liquid

spill for later disposal.

Methods for Cleaning up

Use clean non-sparking tools to collect absorbed material.

6.4. Reference to other sections

Reference to Other Sections SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Advice on Safe Handling

Use personal protective equipment as required. Ensure adequate ventilation, especially in confined areas. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

7.2. Conditions for Safe Storage, including any Incompatibilities

Storage Conditions Keep out of the reach of children. Keep container tightly closed. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from

heat. Keep in properly labeled containers.

Incompatible Materials Water. Alcohols. Strong bases. Strong oxidizing agents. Finely powdered metals.

7.3. Specific End Use(s)

Other Information No information available.

7.4. References to Other Sections

Reference to Other Sections Section 13: DISPOSAL CONSIDERATIONS

Section 10: STABILITY AND REACTIVITY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Exposure Guidelines

. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Limestone CAS 1317-65-3 is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Limestone	-	TWA: 10 mg/m³ total dust	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³
1317-65-3		TWA: 5 mg/m³ respirable	TWA: 5 mg/m³ respirable	STEL: 20 mg/m ³
		dust	fraction	
Dibutyltin dilaurate	STEL: 0.2 mg/m³ Sn	IDLH: 25 mg/m ³ Sn	TWA: 0.1 mg/m³ Sn	TWA: 0.1 mg/m ³
77-58-7	TWA: 0.1 mg/m³ Sn	TWA: 0.1 mg/m ³ except		STEL: 0.2 mg/m ³
	S*	Cyhexatin Sn		
Quartz	TWA: 0.025 mg/m ³	IDLH: 50 mg/m³ respirable	: (30)/(%SiO2 + 2) mg/m ³	TWA: 0.1 mg/m ³
14808-60-7	respirable fraction	dust	TWA total dust	
		TWA: 0.05 mg/m ³	: (250)/(%SiO2 + 5) mppcf	
		respirable dust	TWA respirable fraction	
			: (10)/(%SiO2 + 2) mg/m³	
			TWA respirable fraction	

Chemical Name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m ³	-	TWA: 8 mg/m ³	-
Dibutyltin dilaurate 77-58-7	TWA: 0.1 mg/m³ Skin STEL: 0.2 mg/m³	-	TWA: 0.08 mg/m³ Skin	Skin STEL: 0.2 mg/m³ TWA: 0.1 mg/m³
Quartz 14808-60-7	TWA: 0.05 mg/m ³	-	TWA: 0.08 mg/m ³	TWA: 0.025 mg/m ³

8.2. Exposure Controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Personal protective equipment [PPE]

Eye/Face Protection Tight sealing safety goggles.

G64130 BBWFA Bostiks Best Wood Floor Adh.

Respiratory Protection

Revision Date 13-Jan-2016
Supersedes Date: No information available
Version 2

Skin and Body Protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be

required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Regular

cleaning of equipment, work area and clothing is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical StateLiquidAppearancePasteColorAmber

Odor No information available Odor Threshold No information available

Property Values Remarks • Method

pH No information available
Melting Point/Freezing Point No information available
Boiling Point No information available
Flash Point > 61.1 °C / > 142 °F
Evaporation Rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper Flammability Limit
Lower Flammability Limit
Vapor Pressure
Vapor Density
Specific Gravity
Water Solubility

No information available

Solubility in Other Solvents

Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Kinematic Viscosity
Dynamic Viscosity
Explosive Properties
No information available

9.2. Other Information

Softening PointNo information availableMolecular WeightNo information availableSolvent Content (%)No information available

Solid Content (%) 93.0

Density 1.508 g/cm³ **VOC** 20 G

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical Stability

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

Stable under recommended storage conditions.

10.3. Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization may occur.

10.4. Conditions to Avoid

Heat, flames and sparks. Keep from any possible contact with water. Extremes of temperature and direct sunlight. Storage near to reactive materials.

10.5. Incompatible Materials

Water. Alcohols. Strong bases. Strong oxidizing agents. Finely powdered metals.

10.6. Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on Toxicological Effects

Product InformationNo Data AvailableInhalationNo Data AvailableEye contactNo Data AvailableSkin ContactNo Data AvailableIngestionNo Data Available

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-
Naphtha, petroleum, heavy alkylate 64741-65-7	> 7000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.04 mg/L (Rat)4 h
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	= 2234 mg/kg (Rat)	-	> 640 ppm (Rat)1 h
Dibutyltin dilaurate 77-58-7	= 2071 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
Quartz 14808-60-7	>2000 mg/kg (Rat)	-	-

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

No information available. Symptoms No information available. Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation No information available. No information available. Irritation No information available. Corrosivity Sensitization No information available. **Germ Cell Mutagenicity** No information available. **Reproductive Toxicity** No information available. **Developmental Toxicity** No information available. No information available. **Teratogenicity**

STOT - Single Exposure
STOT - Repeated Exposure
No information available.
No information available.

Chronic Toxicity Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated

exposure. Repeated or prolonged exposure may cause central nervous system damage.

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

Repeated or prolonged contact causes sensitization, asthma and eczemas.

Eyes, Respiratory system, Skin, Central nervous system.

Target Organ EffectsEyes, Respiratory systemAspiration HazardNo information available.CarcinogenicityThe table below indicates

The table below indicates whether each agency has listed any ingredient as a carcinogen. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz	A2	Group 1	Known	X
14808-60-7		·		

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No information available

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulative Potential

No information available.

12.4. Mobility in Soil

No information available.

12.5 Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Disposal of WastesIt is the responsibility of the waste generator to determine the toxicity and physical

properties of the material generated to determine the proper waste identification and

disposal methods in compliance with applicable regulations

Contaminated Packaging Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORT INFORMATION

Note:49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016 Supersedes Date: No information available

Version 2

horandaria aribataria a harandaria wasta an a marina mallutanti "

hazardous substance, a hazardous waste, or a marine pollutant."

DOT

IATA

UN/ID No NA1993

Hazard Class Combustible liquid

Packing Group

Special Provisions IB3, T1, T4, TP1

Description NA1993, Combustible liquid, n.o.s. (Naphtha, petroleum, heavy alkylate), Combustible

liquid, III,

Not regulated

128

Emergency Response Guide

Number

IMDG Not regulated

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B3 - Combustible liquid D2A - Very toxic materials



United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard yes
Fire Hazard yes
Sudden release of pressure hazard No
Reactive Hazard No

California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

G64130 BBWFA Bostiks Best Wood Floor Adh. Revision Date 13-Jan-2016
Supersedes Date: No information available
Version 2

V C1 31011

Chemical Name	CAS No
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Quartz	14808-60-7
N-(trichlloromethylthio)phthalimide	133-07-3
Naphthalene	91-20-3

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Health Hazards 2* Flammability 2 Physical Hazards 0 Personal Protection X

Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 13-Jan-2016

Revision Note Not applicable.

Training Advice No information available

Further information No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet