



OVERNIGHT INSTALL



Avoid loss of revenue with a hassle free installation.

DECADE-LONG GUARANTEE



Maximize your investment with floors guaranteed to last.

SMILE-WORTHY PRICE TAG



Competitive pricing for a superior floor.

OUR FLOORS GO THE DISTANCE BECAUSE WE UNDERSTAND THE DAY-TO-DAY IMPACT ON COMMERCIAL FLOORING.

SLIP-RESISTANT



The most slip resistant safety flooring in the industry... even when wet!

RESPONSIBLY MADE



Made from 98% recycled content, keeping polyvinyls out of our nation's landfills.

IMPACT RESISTANT



Reinforced with random short staple PET fiber, Eco-Grip® is both puncture and impact resistant.

WATERPROOF



Non-porous flooring surface creates a waterproof membrane ideal for above grade installation.

BOOST MORALE



Flexible, anti-fatigue flooring protects your employees' feet, legs, and lower back, while keeping noise levels in the kitchen to a minimum.

BACTERIA & CHEMICAL RESISTANT



Advanced chemistry withstands harsh chemicals and animal fats while a built-in micro-biocide prohibits odor causing mold and mildew.



PEWTER



SLATE



FOREST



GRAPHITE



MOCHA



CHARCOAL



MESA



TERRACOTTA

"It's watertight, easy to clean, you don't have to use mats—it's the perfect product! I have it in both my restaurants and never had to replace it. Easy to stand on, easy to clean and my staff loves it!"

Rob Crenshaw, Owner, Cabo Fish Taco, Charlotte, NC

"Not only did the Eco-Grip flooring system eliminate our need for mats, we were actually surprised at how well it stood up to grease. We also have a landing area that takes a beating from moving heavy equipment around on it. No other floor could possibly stand up to it like Eco-Grip."

Ken Dussinger, Newport Harbor Corporation, Newport, RI

"Labor savings on cleaning mats alone will cover the cost of our Eco-Grip installation in less than 2 years. Plus, our workers are delighted with "no more mats" and the ease of working on Eco-Grip."

Thomas Kacherski, Owner, Crew Restaurant and Bar, Poughkeepsie, NY

"Eco-Grip is a superior product! Hands down a premium floor for any application that requires a durable, slip resistant, easy to manage floor. We look forward to continuing to specify Eco-Grip for all our commercial needs!"

Jeff Storteboom, Dogwood Flooring, Maple Ridge, BC Canada

"You get what you pay for. We are very satisfied with the outcome. The Santa Clara health department was also impressed with the installation."

Jaelyn Nguyen, Unique Cuisine, San Jose, CA

"I love my Eco-Grip Flooring!! I received great advice regarding tying it in to our quarry tile foyer and our wall coverings. The coving on the walls looks great and I really love the stainless steel flashing they did around the floor drains. They even tapered the flooring around the floor drains so that when the water gets close, it goes directly in. It's so much faster to clean and gets so much cleaner than tile, I'll never go back to tile again!"

Kristin Macan, CEC, Mercy Chefs, Portsmouth, VA

Eco-Grip® flooring is produced from recycled materials. Colors may vary slightly from samples.



PRODUCT NAME

ECO-GRIP® SLIP RESISTANT SAFETY FLOORING

MANUFACTURING

Allied Industries International, Inc.
1088 Old Gaffney Hwy, Jonesville, SC 29353
Phone: (864) 674-0018 Fax: (864) 674-0019

PRODUCT DESCRIPTION

Eco-Grip® flooring is manufactured from 98% recycled polyvinyl with short staple fiber reinforcement to increase overall product flexibility and physical strength. Eco-Grip® provides superior shock absorbency and is impact resistant. The unique surface design produces excellent traction even when wet and/or greasy, and the "walk-in" feature provides increased slip resistance over prolonged use. Specifically designed not to shrink or harden when exposed to animal fats or caustic chemicals, Eco-Grip® is manufactured using polymeric plasticizers and is designed to remain stable through extreme temperature changes.

APPLICATIONS

Ideal for areas requiring a durable, waterproof, easy-to-clean floor system, including; commercial kitchens, walk-in coolers, freezers, grocery food prep areas, operating rooms, veterinary clinics, equestrian facilities, locker rooms, weight rooms, gym floors, laboratories, entrance ways, factory and plant floors, multipurpose floors, and as temporary gym floor protection.

SPECIFICATIONS

Size Sheets: 60" x 96" Standard
Thickness: 6.5mm / 4mm
Weight (oz. sq. ft.): 25.16 / 16
Wear layer: 6mm / 3.5mm
Surface Finish: Aggressive slip resistant finish
Colors: Slate, Pewter, Graphite, Charcoal, Forest, Mocha, Mesa, Terracotta

CLEANING INSTRUCTIONS

Each installation includes a cleaning kit (hot water hose, foam gun, degreaser, deck brush & squeegee). Step 1. Remove all loose debris. Step 2. Pre-Rinse the floor with HOT water using your Hot water hose. Step 3. Fill the foam gun reservoir with Eco-Grip® degreaser and apply a liberal amount on the floor. Step 4. Use the deck brush to scrub the floor as needed. Step 5. Allow the degreaser to dwell on the floor for 8 minutes. Step 6. Use HOT water to rinse the floor and the squeegee can be used to direct water toward the floor drains. Refer to the Eco-Grip® Floor Cleaning Manual for additional details.

INSTALLATION

Where to install: Eco-Grip® flooring may be installed on most clean, dry, level and hard substrates. Eco-Grip® may be used for both interior and exterior applications.
Surface Preparation: Surface should be clean and free of debris and registering no more than 98% RH on the relative humidity scale. Eco-Grip® should lay flat and uneven joints and cracks in the substrate should be repaired using an approved underlayment or leveling compound. Eco-Grip® is to be installed following standard Allied installation procedures. Cutting and trimming can be achieved using a standard utility knife or similar razorblade-type tool. Please refer to the Allied Industries Installation Manual for additional details.

ALLIED INDUSTRIES TEST DATA

ASTM G21: Excellent Bacteria & Mildew Resistance
ASTM D412 Tensile Strength: 1694 psi Elongation 130.98%
ASTM D624 Tear Strength: 268 lbs/force/inch Elongation 27.33%
ASTM F970 2000 psi .023 Avg 1500 psi = .014
ANSI B101.3 SCOF = .62 DCOF = .43
ANSI B101.3 DCOF TRL rubber = .72
ASHB 198:2014 SSR Wet = 65
ASTM E662 Smoke Density: DMC 141
Fire Test: NFPA Type I Rated
ASTM D2240 Hardness: 85
Thickness: 6.5mm / 4mm
Weight (oz. sq. ft.): 25.16 / 16
Oxygen Index: 29.0

Eco-Grip® flooring is resistant to the chemicals listed below and Allied Industries will evaluate any chemical not listed which may be present in a particular application. Data based on ASTM D-543; Ammonium Chloride, Calcium Chloride, Fluoroboric Acid, Mineral Spirits, Ammonium Hydroxide, Calcium Hydroxide, Formaldehyde, Motor Oil, Ammonium Nitrate, Calcium Hypochlorite, Gasoline, Muriatic Acid, Ammonium Sulfate, Chicken Fat, Glyoxal, Phosphoric Acid, Amyl Acetate, Chromic Acid, Hexane, Phthalic Acid, Aniline, Citric Acid, Hydrogen Peroxide, Salt Water, Beef Fat, Cutting Oil, Jet Fuel/Diesel Fuel, Sewer Sludge, Benzoic Acid, Detergent Solution, Kerosene, Sodium Hydroxide, Bleach, Diethyl Phthalate, Lacquer Spray Paint, Tannic Acid, Boric Acid, Dilute Sodium Hydroxide, Latex Paint, Triacetin, Butyl Acetate, Ethyl Alcohol, Malic Acid, Varasol, Butyric Acid, Fertilizer Solution, Methyl Alcohol, Vegetable Oil



800-767-5754 Toll Free

**Manufacturing/
International Distribution**
1088 Gaffney Hwy
Jonesville, SC 29353
864-674-0018 ph
864-674-0019 fax

**National Training Center/
SpeedFlex Production**
3013 Bank Street
Charlotte, NC 28203
704-522-0597 ph
704-522-0598 fax

800-767-5754 Toll Free
sales@eco-gripfloor.com
customerservice@eco-gripfloor.com
www.eco-gripfloor.com



Made in USA



ECO-GRIP® Slip resistant safety flooring