(Contd. of page 1)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

· Product identifier

HERCULAN EX 800 { A } · Trade name:

Article number: 708300/25

Application of the substance / the mixture Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HERCULAN B.V.

Energieweg 6 4231 DJ Meerkerk The Netherlands Phone +31 183 354700 Fax: +31 183 354740 e-mail: info@herculan.com

Information department: Enviromental department

Emergency telephone number:

+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz

+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361-H362 Suspected of damaging fertility or the unborn child. May cause harm to breast-fed children.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS08

Signal word Danger

Hazard-determining components of labeling: Quartz (SiO2)

alkanes, C14-17, chloro

Hazard statements May cause cancer.

H361-H362 Suspected of damaging fertility or the unborn child. May cause harm to breast-fed

Precautionary statements P263 Avoid contact during pregnancy/while nursing.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations

Classification system:

NFPA ratings (scale 0 - 4)

Health = 0Fire = 1 Reactivity = 0

HMIS-ratings (scale 0 - 4)

0 Health = 0

Fire = 1 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 2)

HERCUL N

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EX 800 { A }

· vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: There are no additional ingredients present which are classified as hazardous to health or the

environment and on this basis need to be mentioned in this section.

· Dangerous components: 14808-60-7 Quartz (SiO2) 5 - 10% Carc. 1A, H350 25154-52-3 nonylphenol ♠ Repr. 2, H361; ♠ Skin Corr. 1B, H314; ♠ Acute Tox. 4, H302 < 0.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints. · After skin contact: Generally the product does not irritate the skin.

· After eye contact:



Rinse opened eye for several minutes under running water.

After swallowing:

Information for doctor:

Most important symptoms and effects, both

acute and delayed

Indication of any immediate medical attention

and special treatment needed

No further relevant information available. No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:



CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

Special hazards arising from the substance or

During heating or in case of fire poisonous gases are produced. Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Protective equipment: Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment

and emergency procedures

· Environmental precautions:

Methods and material for containment and

cleaning up:

Mount respiratory protective device. Do not allow to enter sewers/ surface or ground water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EX 800 { A }

(Contd. of page 2)

7 Handling and storage

Handling:

Precautions for safe handling No special measures required

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against

explosions and fires: Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and

receptacles:

No special requirements.

Information about storage in one common storage facility:

Further information about storage conditions: Protect from frost.

Not required.

Keep receptacle tightly sealed. Store in dry conditions. Store in a cool place.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of

technical systems:

No further data: see item 7.

· Control parameters

Components with limit values that require

monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have

to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:

Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when high concentrations are present.

Recommended filter device for short term use:

Protection of hands:

Material of gloves

Combination filter A-P2



Protective aloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance

and has therefore to be checked prior to the application.

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves

and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the

penetration time is recommended

(Contd. on page 4)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EX 800 { A }

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR Natural rubber, NR

Eye protection:

Body protection:

Tightly sealed goggles



Protective work clothing

9 Ph	vsical	and o	:hemica	al pro	perties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Color: According to product specification

Odor: Characteristic · Odor threshold:

Not determined.

· pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 201 °C (394 °F)

Flash point: 255 °C (491 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: > 255 °C (> 491 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard

· Explosion limits:

Lower: Not determined Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 1 hPa (1 mm Hg)

Density at 20 °C (68 °F): 1.4207 g/cm3 (11.856 lbs/gal)

Relative density Not determined. Vapor density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dvnamic: Not determined Kinematic: Not determined.

Solvent content:

Organic solvents: 0.0 % Water: 0.0 %

Solids content: 69.2 %

Other information No further relevant information available.

(Contd. on page 5)

Page 4/8

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EX 800 { A }

(Contd. of page 4)

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be

avoided:

Possibility of hazardous reactions

Conditions to avoid

· Incompatible materials:

· Hazardous decomposition products:

No dangerous reactions known. No further relevant information available.

No further relevant information available. No dangerous decomposition products known.

No decomposition if used according to specifications.

11 Toxicological information

· Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

25154-52-3 nonylphenol

Oral LD50 500 mg/kg (rat)

Primary irritant effect:

on the skin: on the eye:

Sensitization:

Additional toxicological information:

No sensitizina effects known.

The product shows the following dangers according to internally approved calculation methods

for preparations:

No irritant effect.

No irritating effect.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)					
	Quartz (SiO2)	1			
14807-96-6	Talc (Mg3H2(SiO3)4)	3			
1318-02-1	Zeoliet	3			
14808-60-7	Quartz (SiO2)	1			
1330-20-7	xylene (mix)	3			
13463-67-7	titanium dioxide	2B			
100-41-4	ethylbenzene	2B			
NTP (National Toxicology Program)					

NTP (National Toxicology Program)

14808-60-7	Quartz (SIO2)]
14808-60-7	Quartz (SiO2)]
		_ 1

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Aquatic toxicity:

85535-85-9 alkanes, C14-17, chloro

Accute LC50 1 mg/L (Gammarus pulex)

Acute EC50 0.006 mg/L (Daphnia Magna)

Persistence and degradability

Behavior in environmental systems:

Bioaccumulative potential Mobility in soil

Additional ecological information:

General notes:

No further relevant information available.

No further relevant information available No further relevant information available.

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EX 800 { A }

(Contd. of page 5)

Page 6/8

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PRT: · vPvB:

Not applicable. Not applicable.

· Other adverse effects

No further relevant information available.

3 Disposal considerations

· Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach

· Uncleaned packagings:

· Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper

14 Transport information

· UN-Number

DOT, ADR, ADN, IMDG, IATA Void

· UN proper shipping name

DOT. ADR. ADN. IMDG. IATA Void

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Void

Packing group

DOT, ADR, IMDG, IATA

Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable

· Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code

Not applicable

· UN "Model Regulation":

Void

Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· Section 355 (extremely hazardous substances):

None of the ingredient is listed

· Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural

25154-52-3 nonylphenol

· TSCA (Toxic Substances Control Act):

8001-79-4 Castor oil

7727-43-7 barium sulphate, natural

31831-53-5 2-oxepanone, polymer with 1.4 butandiol

14808-60-7 Quartz (SiO2)

14807-96-6 Talc (Mg3H2(SiO3)4)

37625-56-2 2-Oxepanone, polymer with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol

25190-06-1 Polytetramethyleneetherglycol

(Contd. on page 7

Page 7/8

A4

A2

A4

A4

АЗ

3B

(Contd. on page 8)

acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016 Trade name: HERCULAN EX 800 { A } (Contd. of page 6) 68186-91-4 Copper chromite spinel pigment Cu(Cr,Fe)2O4 25265-71-8 oxydipropanol 25154-52-3 nonylphenol 110-63-4 butane-1,4-diol 69011-20-7 Styreen-Divinylbenzen-Copolymer 502-44-3 hexan-6-olide Proposition 65 Chemicals known to cause cancer: 14808-60-7 Quartz (SiO2) Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: None of the ingredients is listed. Cancerogenity categories EPA (Environmental Protection Agency) 7727-43-7 barium sulphate, natural D. CBD(inh), NL(oral) 1330-20-7 xylene (mix) 100-41-4 ethylbenzene TLV (Threshold Limit Value established by ACGIH) 14808-60-7 Quartz (SiO2) 14807-96-6 Talc (Mg3H2(SiO3)4) 14808-60-7 Quartz (SiO2) 1330-20-7 xylene (mix) 13463-67-7 titanium dioxide 100-41-4 ethylbenzene MAK (German Maximum Workplace Concentration) 14808-60-7 Quartz (SiO2) 14807-96-6 Talc (Mg3H2(SiO3)4) 14808-60-7 Quartz (SiO2) 13463-67-7 titanium dioxide 100-41-4 ethylbenzene NIOSH-Ca (National Institute for Occupational Safety and Health) 14808-60-7 Quartz (SiO2) 14808-60-7 Quartz (SiO2) 13463-67-7 titanium dioxide GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms GHS08 Signal word Danger · Hazard-determining components of labeling: Quartz (SiO2) alkanes, C14-17, chloro Hazard statements H350 May cause cancer. H361-H362 Suspected of damaging fertility or the unborn child. May cause harm to breast-fed Precautionary statements P263 Avoid contact during pregnancy/while nursing. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P264 Wash thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P201 Obtain special instructions before use.

P202

Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN EX 800 { A }

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· National regulations:

Additional classification according to Decree

on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in

this preparation. Exceptions can be made by the authorities in certain cases.

· Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· voc

· VOC EU [%] 0.03 % · VOC EU [g/l] 0.5 g/l · VOC USA 0.5 g/l / 0.00 lb/ql

· VOC CH 0.03 %

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental Department

· Contact:

· Date of preparation / last revision 08/02/2016 / 24

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

Dr. Michael Kissel

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Carc. 1A: Carcinogenicity - Category 1A

Repr. 2: Reproductive toxicity – Category 2

* Data compared to the previous version

altered.

Page 8/8

(Contd. of page 7)