Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

1 Identification

· Product identifier

HERCULAN Filler S · Trade name:

Article number: 266101 1/13

Application of the substance / the mixture Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HERCULAN B.V. Energieweg 6

4231 DJ Meerkerk The Netherlands Phone +31 183 354700 Fax: +31 183 354740 e-mail: info@herculan.com

Information department: Enviromental department

Emergency telephone number:

+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz

+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS08

Signal word Danger

Hazard-determining components of labeling: Quartz (SiO2)

Hazard statements

H350 May cause cancer. Precautionary statements

Wear protective gloves/protective clothing/eye protection/face protection.

P201 Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up. P501

Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Classification system:

NFPA ratings (scale 0 - 4)

Health = 0

Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)

0 Health = 0 Fire = 0Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: There are no additional ingredients present which are classified as hazardous to health or the environment and on this basis need to be mentioned in this section.

Dangerous components:

14808-60-7 Quartz (SiO2)

(Contd. on page 2)

Carc. 1A, H350 50 - 100%



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN Filler S

(Contd. of page 1) For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Additional information:

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

· After eve contact:

Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both

acute and delayed

Indication of any immediate medical attention

and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:



Not required.

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire

· Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

No further relevant information available

· Personal precautions, protective equipment

and emergency procedures

Environmental precautions:

Reference to other sections

Methods and material for containment and

cleaning up:

No special measures required.

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Keep respiratory protective device available.

Open and handle receptacle with care.

Information about protection against

explosions and fires:

· Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and

receptacles:

No special requirements.

Information about storage in one common storage facility:

Not required. Further information about storage conditions: Protect from frost.

Keep receptacle tightly sealed.

(Contd. on page 3)

acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN Filler S

(Contd. of page 2)

Store in dry conditions. Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of

technical systems:

No further data: see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

14808-60-7 Quartz (SiO2)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m3

*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m3

*as respirable fraction

· Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:



Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when high concentrations are present.

Recommended filter device for short term

· Protection of hands:

Combination filter A-P2

Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance

and has therefore to be checked prior to the application.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended

As protection from splashes gloves made of the following materials are suitable:

Penetration time of glove material

Nitrile rubber, NBR Natural rubber, NR

Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN Filler S

(Contd. of page 3)

Page 4/7

Information on basic physical and chemic	al properties	
General Information		
Appearance:		
Form:	Solid	
Color:	According to product specification	
Odor: Odor threshold:	Characteristic Not determined.	
pH-value:	Not applicable.	
Change in condition Melting point/Melting range:	1713 °C (3115 °F)	
Boiling point/Boiling range:	>999 °C (>1830 °F)	
Flash point:		
Flammability (solid, gaseous):	Not applicable.	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Not determined.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 1732 °C (3150 °F):	13.5 hPa (10 mm Hg)	
Density at 20 °C (68 °F):	2.7 g/cm³ (22.532 lbs/gal)	
Bulk density at 20 °C (68 °F):	1400 kg/m³	
Relative density	Not determined.	
Vapor density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with Water:		
	Insoluble.	
Partition coefficient (n-octanol/water):	Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Solvent content:		
Organic solvents: Water:	0.0 % 0.0 %	

10 Stability and reactivity

Reactivity

No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be

avoided:

· Possibility of hazardous reactions

No dangerous reactions known.

· Conditions to avoid Incompatible materials: No further relevant information available. No further relevant information available.

No decomposition if used according to specifications.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

No dangerous decomposition products known.

Trade name: HERCULAN Filler S

11 Toxicological information

Information on toxicological effects

· Hazardous decomposition products:

- Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect. on the eye: No irritating effect. Sensitization:
- No sensitizing effects known. Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

14808-60-7 Quartz (SiO2)

NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Aquatic toxicity:

Persistence and degradability

No further relevant information available. No further relevant information available.

Behavior in environmental systems:

· Bioaccumulative potential

No further relevant information available. No further relevant information available.

Generally not hazardous for water

Mobility in soil

Additional ecological information: General notes:

Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

Other adverse effects

No further relevant information available.

Void

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach

sewage system.

Uncleaned packagings:

Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

4 Transport information

· UN-Number

DOT, ADR, ADN, IMDG, IATA

UN proper shipping name

DOT, ADR, ADN, IMDG, IATA Void

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

trade name: PERCULAIN FILIEF 3		
	(Contd. of page 5)	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Void	
· Packing group · DOT, ADR, IMDG, IATA	Void	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	d Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

UEBOUL AN EUL O

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

· Chemicals known to cause cancer:

All ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

14808-60-7 Quartz (SiO2)

· MAK (German Maximum Workplace Concentration)

14808-60-7 Quartz (SiO2)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

All ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms GHS08 · Signal word Danger

· Hazard-determining components of labeling: Quartz (SiO2)

· Hazard statements

H350 May cause cancer. · Precautionary statements P280

P201 Obtain special instructions before use

Wear protective gloves/protective clothing/eye protection/face protection.

Do not handle until all safety precautions have been read and understood. P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 7)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN Filler S

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· National regulations:

Additional classification according to Decree

on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).

Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in

this preparation. Exceptions can be made by the authorities in certain cases.

· Water hazard class: Generally not hazardous for water.

· voc

· VOC EU [%] 0.00 %

· VOC USA 0.0 g/l / 0.00 lb/gl

· VOC CH 0.00 %

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental Department

Dr. Michael Kissel · Date of preparation / last revision 08/02/2016 / 12

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) PRT: Persistent Rinaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Carc. 1A: Carcinogenicity – Category 1A

* Data compared to the previous version

altered.

