Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

1 Identification

· Product identifier

HERCULAN LY 2000 { B } · Trade name:

Article number:

Application of the substance / the mixture Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HERCULAN B.V.

Energieweg 6 4231 DJ Meerkerk The Netherlands Phone +31 183 354700 Fax: +31 183 354740 e-mail: info@herculan.com

Information department: Enviromental department

Emergency telephone number:

+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz

+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN

2 Hazard(s) identification

Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Precautionary statements

Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms GHS05, GHS06, GHS07

Signal word Danger

Hazard-determining components of labeling: Benzvl alcohol

polyoxyalkyleenamin

3-aminomethyl-3,5,5-trimethylcyclohexylamine

trimethylhexane-1,6-diamine

Hazard statements H302+H332 Harmful if swallowed or if inhaled.

H311 Toxic in contact with skin. H314

Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. P260 Do not breathe dusts or mists.

P280 Wear protective gloves / protective clothing.

P280 Wear eye protection / face protection. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

(Contd. on page 2)

HERCULAN

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

(Contd. of page 1)

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor.

P310 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

NFPA ratings (scale 0 - 4)

· HMIS-ratings (scale 0 - 4)

Health = 3Fire = 1 Reactivity = 0

Health = 3Fire = 1

Reactivity = 0

Other hazards

· Results of PBT and vPvB assessment

· PRT: · vPvB:

Not applicable. Not applicable

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Description:

There are no additional ingredients present which are classified as hazardous to health or the

environment and on this basis need to be mentioned in this section.

· Dangerous components: 100-51-6 Benzyl alcohol 25 - 100% Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2A, H319 3-aminomethyl-3.5.5-trimethylcyclohexylamine 10 - 25% Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 polyoxvalkyleenamin 10 - 25% Acute Tox. 3, H301; Acute Tox. 3, H311; Skin Corr. 1B, H314; Eye Dam. 1, H318 25620-58-0 trimethylhexane-1,6-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; 🗘 Acute Tox. 4, H302; Skin Sens. 1, H317

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

After inhalation:

Immediately remove any clothing soiled by the product.



Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. · After swallowing: Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 3)

Printing date 08/02/2016

Page 3/10

Reviewed on 08/02/2016

(Contd. of page 2)

Page 4/10 Safety Data Sheet

acc. to OSHA HCS Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

(Contd. of page 3)

Trade name: HERCULAN LY 2000 { B }

Information for doctor:

Most important symptoms and effects, both

acute and delayed

No further relevant information available.

Indication of any immediate medical attention

and special treatment needed No further relevant information available

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:



CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

Special hazards arising from the substance or

mixture

During heating or in case of fire poisonous gases are produced. Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment

and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away. Do not allow to enter sewers/ surface or ground water.

Environmental precautions: Methods and material for containment and

cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

See Section 7 for information on safe handling. Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and

receptacles:

No special requirements.

Information about storage in one common

storage facility: Not required.

Further information about storage conditions: Protect from frost.

Keep receptacle tightly sealed. Store in dry conditions.

Store in a cool place

Specific end use(s) No further relevant information available.

HERCUL

8 Exposure controls/personal protection

· Additional information about design of

technical systems:

· Control parameters

· Components with limit values that require

monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit

No further data: see item 7.

At this time, the other constituents have no known exposure limits.

100-51-6 Benzvl alcohol

WEEL Long-term value: 10 ppm

Additional information:

The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work. Store protective clothing separately.

Avoid contact with the eves. Avoid contact with the eves and skin. Do not eat, drink, smoke or sniff while working.

· Breathing equipment:



Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when high concentrations are present.

Recommended filter device for short term

Protection of hands:

· Material of gloves

Combination filter A-P2

Protective gloves The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation. The selection of the suitable gloves does not only depend on the material, but also on further

marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance

and has therefore to be checked prior to the application.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· As protection from splashes gloves made of the following materials are suitable:

· Penetration time of glove material

Nitrile rubber, NBR Natural rubber, NR

Eye protection:

Body protection:



Tightly sealed goggles



Protective work clothing

(Contd. on page 5)

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

(Contd. of page 4)

9 Physical and chemical properties	
· Information on basic physical and chemical properties	
General Information	, p. spo. 1100
Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	205 °C (401 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	435 °C (815 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	0.1 hPa
· Density at 20 °C (68 °F):	1 g/cm³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	50 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Water:	0.0 %
Solids content:	22.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

· Thermal decomposition / conditions to be

avoided:

No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

· Hazardous decomposition products: No dangerous decomposition products known. (Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

100-51-6 Benzvl alcohol

LD50 1230 mg/kg (rat) LD50 Dermal 2000 ma/ka (rabbit) Inhalative LC50/4 h 4178 mg/l (rat)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Inhalative LC50/4 h 46 mg/l (rat)

Primary irritant effect:

on the skin: Caustic effect on skin and mucous membranes.

on the eye: Strong caustic effect.

Strong irritant with the danger of severe eye injury.

Sensitization: Sensitization possible through skin contact.

· Additional toxicological information: The product shows the following dangers according to internally approved calculation methods

for preparations: Toxic Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of

perforation of esophagus and stomach.

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

100-51-6 Benzyl alcohol

Accute LC50 | 10 mg/L (Lepomis macrochirus (Zonnebaars))

55-400 mg/L (Daphnia Magna) (24 h) Acute EC50

LogPow 1.1 BCF (n-octanol/water) OECD 209 2100 ma/l

OECD 301 C 92-96 % (14 d)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

EbC50 37 mg/l (scenedesmus subspicatus) (72 h)

Accute LC50 110 mg/L (leuciscus idus) (96 h) Acute EC50 23 mg/L (Daphnia Magna) (48 h) EC10 1120 mg/l (Bacterie) (18 h) LogPow 0.79 BCF (n-octanol/water)

OECD 301 A 8 % (28 d)

OECD 303 A 42 % (3 h)

Persistence and degradability

No further relevant information available.

· Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

Mobility in soil

No further relevant information available.

Additional ecological information:

General notes: Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

vPvB: Not applicable.

Other adverse effects

Not applicable.

No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach

Uncleaned packagings:

Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper

Amines, liquid, corrosive, n.o.s. (Isophoronediamine,

cleaning.

4 Transport information

· UN-Number

DOT, ADR, IMDG, IATA

UN2735

UN proper shipping name

· DOT

Polyoxypropylenediamine, ADR 2735 Amines, liquid, corrosive, n.o.s. (Isophoronediamine,

Polyoxypropylenediamine) IMDG, IATA

AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE,

8

Polyoxypropylenediamine)

· Transport hazard class(es)

DOT



Class 8 Corrosive substances

Label

ADR



Class 8 (C7) Corrosive substances

· Label

IMDG. IATA



Class 8 Corrosive substances

Label

(Contd. on page 8)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B } (Contd. of page 7) Packing group DOT, ADR, IMDG, IATA · Environmental hazards: Marine pollutant: No Special precautions for user Warning: Corrosive substances Danger code (Kemler): · EMS Number: F-A.S-B Segregation groups Alkalis Stowage Category Segregation Code SG35 Stow "separated from" acids. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable Transport/Additional information: · ADR · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml IMDG Limited quantities (LQ) · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, POLYOXYPROPYLENEDIAMINE), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

100-51-6 Benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

25620-58-0 trimethylhexane-1,6-diamine

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS

Page 9/10

(Contd. of page 8)

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms GHS05, GHS06, GHS07

Signal word

· Hazard-determining components of labeling: Benzyl alcohol polyoxyalkyleenamin

3-aminomethyl-3,5,5-trimethylcyclohexylamine

trimethylhexane-1.6-diamine

Hazard statements H302+H332 Harmful if swallowed or if inhaled.

> H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements P260 Do not breathe dusts or mists.

P280 Wear protective gloves / protective clothing. P280

Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P301+P330+P331 If swallowed: Rinse mouth, Do NOT induce vomiting.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

National regulations:

Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

VOC

VOC EU [%] 0.00 % VOC USA 0.0 q/l / 0.00 lb/ql

· VOC CH

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental Department · Contact: Dr. Michael Kissel

· Date of preparation / last revision 08/02/2016 / 8

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hydienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN LY 2000 { B }

(Contd. of page 9) ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

I D50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TI V: Threshold I imit Value

PFI : Permissible Exposure I imit REL: Recommended Exposure Limit

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation — Category 1B
Eye Dam. 1: Serious eye damage/eye irritation — Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation — Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

* Data compared to the previous version

Page 10/10