

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

1 Identification

· Product identifier

HERCULAN UN 700 { B } · Trade name:

Article number: 901411/22

Application of the substance / the mixture Coating compound/ Surface coating/ paint

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HERCULAN B.V.

Energieweg 6 4231 DJ Meerkerk The Netherlands Phone +31 183 354700 Fax: +31 183 354740 e-mail: info@herculan.com

Information department: Enviromental department

Emergency telephone number:

+49 (0) 6131 19240 [24 h - 365 d] - Giftinformationszentrale Mainz

+31 (0) 183 354 700 [Mo - Fr. 8 - 17 o'clock] - HERCULAN

2 Hazard(s) identification

Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction. Skin Sens. 1

STOT SE 3 H335 May cause respiratory irritation.

Label elements

GHS label elements

Precautionary statements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms GHS07, GHS08

Signal word Danger

Hazard-determining components of labeling: 4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

diphenylmethane-4,4'-diisocyanate

Hazard statements H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation

H373 May cause damage to organs through prolonged or repeated exposure.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

(Contd. on page 2)

HERCULAN

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 1

P202 Do not handle until all safety precautions have been read and understood. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P312 Call a POISON CENTER/doctor if you feel unwell. P321

Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell. P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

NFPA ratings (scale 0 - 4)

· HMIS-ratings (scale 0 - 4)



P501

P342+P311

Health = 1Fire = 1 Reactivity = 0

Health = *2

Fire = 1 Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PRT: · vPvR· Not applicable.

Not applicable

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Description:

There are no additional ingredients present which are classified as hazardous to health or the environment and on this basis need to be mentioned in this section

Dangerous components: 4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

\gg Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; 🕦 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skir Sens. 1. H317: STOT SE 3. H335 101-68-8 diphenylmethane-4,4'-diisocyanate 25 - 100%

🔈 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; 🚺 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skir Sens. 1, H317; STOT SE 3, H335

Additional information:

For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

· After skin contact:

Immediately remove any clothing soiled by the product.



Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air and to be sure call for a doctor

In case of unconsciousness place patient stably in side position for transportation.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water

 After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a

doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

50 - 100%

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

Information for doctor: Most important symptoms and effects, both

acute and delayed No further relevant information available.

Indication of any immediate medical attention

and special treatment needed No further relevant information available

5 Fire-fighting measures

Extinguishing media

· Suitable extinguishing agents:



CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

Special hazards arising from the substance or

mixture

During heating or in case of fire poisonous gases are produced. Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment

and emergency procedures

Mount respiratory protective device. Do not allow to enter sewers/ surface or ground water.

Environmental precautions:

Reference to other sections

Methods and material for containment and

cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care. Prevent formation of aerosols.

Information about protection against

explosions and fires:

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and

receptacles:

No special requirements.

Information about storage in one common

storage facility:

Not required.

Further information about storage conditions: Protect from frost.

Keep receptacle tightly sealed. Store in dry conditions. Store in a cool place.

Specific end use(s) No further relevant information available.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 3)

Page 4/9

8 Exposure controls/personal protection

· Additional information about design of

technical systems:

· Control parameters

· Components with limit values that require monitoring at the workplace:

No further data: see item 7.

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit

At this time, the remaining constituent has no known exposure limits.

101-68-8 diphenylmethane-4.4'-diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

REL Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m3, 0.02* ppm *10-min

TLV Long-term value: 0.051 mg/m³, 0.005 ppm

Additional information:

The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

· Breathing equipment:



Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation. Use suitable respiratory protective device when high concentrations are present.

· Recommended filter device for short term

· Protection of hands:

Material of gloves

Combination filter A-P2



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

The selection of the suitable gloves does not only depend on the material, but also on further

marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR Natural rubber, NR

Eye protection:

Body protection:



Tightly sealed goggles

Protective work clothing

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 4)

Information on basic physical and chemical General Information	properties	
		
Appearance:		
Form: Color:	Fluid	
· Odor:	According to product specification Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition	Tot determined.	
Melting point/Melting range:	< 0 °C (< 32 °F)	
Boiling point/Boiling range:	>300 °C (>572 °F)	
· Flash point:	230 °C (446 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	520 °C (968 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	0.4 Vol %	
Upper:	0.0 Vol %	
· Vapor pressure:	Not determined.	
· Density at 20 °C (68 °F):	1.22 g/cm³ (10.181 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Water:	0.0 %	
· Other information	No further relevant information available.	

	l react	

Reactivity No further relevant information available.

Chemical stability

· Thermal decomposition / conditions to be

avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known. Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available. Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 5)

Page 6/9

11 Toxicological information

· Information on toxicological effects

LD50

Acute toxicity:

Dermal

Oral

LD/LC50 values that are relevant for classification:	
--	--

9016-87-9 4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

>10000 mg/kg (rat)

>9400 mg/kg (rabbit)

101-68-8 diphenylmethane-4,4'-diisocyanate		
		negative
Irritation of skin	OECD 406	not sensitising (Guinea pig)
	without guidelines	sensitising (rat)
	OECD 453	negative (rat)
Inhalative	LC50/4 h	310 mg/l (rat)

LD50

E	Dermal	LD50	>9400 mg/kg (rabbit)
I	nhalative	LC50/4 h	0.31 mg/l (rat)
		LC50/1 h	2.24 mg/l (rat)
		OECD 453	positive (rat) (2 years - 5 days per week)
		without guidelines	Sensitising (Guinea pig)
1	rritation of skin	OECD 406	Not sensitising (Guinea pig)
		OECD 474	- (Mammalian Erythrocyte Micronucelus Test)

>2000 mg/kg (rat)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eve: Irritating effect.

Sensitization: Sensitization possible through inhalation.

Sensitization possible through skin contact. · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

п	-		
l	9016-87-9	4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan	3
l	101-68-8	diphenylmethane-4,4'-diisocyanate	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

Aquatic toxicity:

9016-87-9 4.4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

5010 01 0 4,4 metrificing at 1500 garage 150 meters 4 mengoes dadi van	
LogPow	200 BCF
OECD 202	> 1000 mg/l (Daphnia Magna)
OECD 203	> 1000 mg/l (fish)
OECD 209	> 100 mg/l (Bacterie)
OECD 211	> 10 mg/l (Daphnia Magna)
OECD 302 C	0 %

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 6) 101-68-8 diphenylmethane-4,4'-diisocyanate

200 BCF LoaPow OECD 202 > 1000 mg/l (daphnia)

> 1000 mg/l (fish)

OECD 203 OECD 209 > 100 mg/l (Bacterie)

OECD 211 > 10 mg/l (Daphnia Magna) OECD 302 C 0 % (Modified MITI Test (II))

Persistence and degradability

Behavior in environmental systems: Bioaccumulative potential

Mobility in soil

Additional ecological information:

General notes:

Results of PBT and vPvB assessment

· PBT: vPvB:

Other adverse effects

No further relevant information available

No further relevant information available. No further relevant information available

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system

Not applicable. Not applicable.

No further relevant information available.

13 Disposal considerations

· Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper


4 Transport information

· UN "Model Regulation":

· UN-Number · DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA · Class	Void
· Packing group · DOT, ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	l Not applicable.

Void

(Contd. on page 8)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 7)

CBD

D, CBD

Page 8/9

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

9016-87-9 4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

101-68-8 diphenylmethane-4,4'-diisocyanate

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

MAK (German Maximum Workplace Concentration)

9016-87-9 4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

101-68-8 diphenylmethane-4,4'-diisocyanate

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms

· Signal word Danger

· Hazard-determining components of labeling: 4,4'-methylenediphenyl di-isocyanate isomeren + mengsels daarvan

GHS07, GHS08

diphenylmethane-4,4'-diisocyanate Hazard statements

H332 Harmful if inhaled. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure. P260

· Precautionary statements Do not breathe dust/fume/gas/mist/vapors/spray.

P284 [In case of inadequate ventilation] wear respiratory protection. P280

Wear protective gloves. P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

(Contd. on page 9)

HERCUL

Safety Data Sheet acc. to OSHA HCS

Printing date 08/02/2016 Reviewed on 08/02/2016

Trade name: HERCULAN UN 700 { B }

(Contd. of page 8)

Page 9/9

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell. P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· National regulations:

· Technical instructions (air):

Class | Share in % 97.5

Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

0.00 %

Other regulations, limitations and prohibitive

regulations

No sales to private

· voc VOC EU [%]

VOC USA 0.0 g/l / 0.00 lb/gl

VOC CH 0.00 %

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental Department

Contact: Dr. Michael Kissel

Date of preparation / last revision 08/02/2016 / 21

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data compared to the previous version altered.