

PORTABLE BANKED TRACKS

VERSATILITY AND PERFORMANCE



THE WORLD'S FIRST PORTABLE BANKED MODULTRACK WAS INSTALLED IN 1984 AT THE WORLD MEMORIAL HALL IN KOBE, JAPAN. ALL OF MONDO'S MODULTRACK SOLUTIONS ARE DESIGNED WITH FULLY ADJUSTABLE STRUCTURES TO GUARANTEE QUICK ASSEMBLY AND COMPLIANCE WITH INTERNATIONAL REGULATIONS, EVEN WHEN THE SUPPORTING SURFACE IS NOT STATE-OF-THE-ART.

EASY INSTALLATION FOR MAXIMAL PERFORMANCE

With its claw-locking mechanism, the structure's frame can be assembled and disassembled quickly and easily with no screws or bolts, guaranteeing consistent tightness and perfect dimensional accuracy, installation after installation. The process can be completed in a few short days. Once disassembled, the track is easily stored in a warehouse and the entire area can be used for other purposes.

MONDOTRACK WS 13.5 MM I / VERSION

I / VERSION

THICKNESS

13,5 mm

WEIGHT

12,6 kg/m²


LENGTH

6÷15 m


HEIGHT

122÷160 cm


COLOR RANGE



P18



P58




P14



P85




P31



P30



P10



P70

SPORTFLEX SUPER X 6 MM I / VERSION

I / VERSION

THICKNESS

6 mm

WEIGHT

6,2 kg/m²

LENGTH

6÷20 m

HEIGHT

122÷183 cm

COLOR RANGE

INDOOR&OUTDOOR



P30



P58



P10



P14



P18



P70



P85



P31

SPORTFLEX SUPER X 8 MM I / VERSION

I / VERSION

THICKNESS

8 mm

WEIGHT

8,0 kg/m²

LENGTH

6÷18 m

HEIGHT

122÷183 cm

COLOR RANGE

INDOOR&OUTDOOR




P30




P58



P10




P14



P18



P70



P85



P31

SPORTFLEX SUPER X 11 MM I / VERSION

I / VERSION

THICKNESS

11 mm

WEIGHT

11,3 kg/m²

LENGTH

6÷17 m

HEIGHT

122÷160 cm

COLOR RANGE

INDOOR&OUTDOOR




P30




P58



P10



P14



P18



P70



P85



P31